



LOAD  
CIRCUIT  
BREAKER

OIL  
FILL

COOLANT FILL

AIR  
CLEANER

1.50 [38.1] MIN.  
CLEARANCE

FUEL FILTER

OIL FILTER

OIL FILL

COOLANT FILL/  
RESEVOIR

COOLING  
AIR INTAKE

**Stadco**  
GENERATORS

**Stadco**  
GENERATORS

FUEL  
CONNECTIONS

25.13 [638.2]

BATTERY  
TERMINALS

MOUNTING  
HOLES

HOT AIR  
DISCHARGE

9.00 [228.6]

9.00 [228.6]

5.00 [127.0]

8.63 [219.1]

17.25 [438.2]

18.00 [457.2]

EXHAUST  
CONNECTION

0.31 [7.9]

28.00 [711.2]

30.63 [778.0]

ENGINE END

SERVICE SIDE

INFORMATION CONTAINED HEREIN IS DEEMED  
RELIABLE BUT NOT GUARANTEED

THIS PRINT IS A CONFIDENTIAL DISCLOSURE  
THE SUBJECT MATTER OF WHICH IS THE  
PROPERTY OF STAUFFER DIESEL INC.

TITLE:		CELLPAC MODEL CP7	
THE FOLLOWING TOLERANCES APPLY UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS ARE INCH [mm]		<b>STADCO</b> <b>STAUFFER DIESEL INC</b> EPHRATA, PA., U.S.A. 17522	
DECIMALS	ANGLES		
.X ± .060	± 2°	DRAWN BY:	SCALE:
.XX ± .030	FRACTIONS	TJS	FULL
.XXX ± .010	± 1/32	GROUP NO.	ORDER NO.
MACHINED SURFACES ARE 125 ✓		DATE:	10/25/06
DRILLED HOLES +.008 - .003		GROUP NO.	ORDER NO.
PUNCHED HOLES ±.016		1 OF 1	DRAWING NO.
			12645